

Patent Abstracts of Japan

PUBLICATION NUMBER : 63292805
PUBLICATION DATE : 30-11-88


APPLICATION DATE : 26-05-87
APPLICATION NUMBER : 62128594

APPLICANT : MATSUSHITA ELECTRIC WORKS LTD;

INVENTOR : NAKAJO HIROSHI;

INT.CL. : H03G 3/20 H04L 27/06

TITLE : AM DATA WIRELESS RECEIVER



ABSTRACT : PURPOSE: To widen a dynamic range even when a transmission area is expanded and to realize reception with superior sensitivity, by amplifying a weak signal by controlling amplification degree by a first demodulator, and outputting a strong signal by suppressing the amplification degree by a second demodulator.

CONSTITUTION: The first demodulator I is provided with an AGC function, therefore, it is formed so that the amplification degree of an intermediate frequency amplifier 105 can be controlled by outputting an AGC signal corresponding to a detector 1108 with superior detecting efficiency which detects the weak signal and a signal to be inputted to the detector 1108. The second demodulator II is constituted of a simple and inexpensive envelope detector in which a diode D, a capacitor C, and a resistor are combined, etc. In such a way, a signal being damped and weakened because of transmission from a remote place is amplified by the demodulator I, and the strong signal from a near place is amplified by the demodulator II. Therefore, the signal emitted both from the remote place or the near place can be received with high sensitivity.

COPYRIGHT: (C) JPO

Best Available Copy